

FM Omega™ Monitor



Features:

- cast-in turning vanes for a more efficient flow
- 360° horizontal and 150° vertical travel
- friction loss: 10 PSI at 800 GPM(.7 bar at 3030 LPM)
- 4 bolt hole pattern on flange
- Factory Mutual approved

Size	Inlet	Outlet	Waterway	Flow	Brass Part #	Price/E
17" x 11½"	3" flange	2½" MNST	3"	1250 GPM	AK3526-300FL	\$7073.15

Brass Monitor Nozzle



Features:

- fixed teeth
- combination Straight, Stream and Fog - no shutoff
- fixed gallonage master stream nozzle
- factory set at 500 GPM (1900 lpm) field changeable to 300 or 700 GPM (1140 or 2660 LPM)
- maximum operating pressure: **100 PSI** (water only)

Size	Thread	90° Spray GPM @100 PSI	Brass Part #	Price/E
2½"	NST (NH)	NST (NH)	AK4450NST	\$2428.95

FM Steel FirePro™ Monitor



Features:

- seamless 2½" monitor - rated at 750 GPM
- carbon steel construction, stainless steel discharge tip and ball bearings
- 360° horizontal and 140° vertical travel
- red epoxy finish standard
- 150# ASA raised face 4" flange
- Factory Mutual approved

Size	Inlet	Outlet	Waterway	Flow	Carbon Steel Part #	Price/E
22" x 13"	4" flange	2½" MNST	2½"	750 GPM	FP475S	\$3780.00

FM Master Stream Nozzles



Features:

- factory set at 500 GPM
- featuring a straight stream to fog 'quick throw' pattern change
- constant gallonage
- Factory Mutual approved

Size	Thread	Material	Part #	Price/E
2½"	NST (NH)	brass	FP500B	\$2749.10
2½"	NST (NH)	aluminum	FP500A	2285.20

P

Street Cleaning Nozzles



Feature:

- welded fabrication

Size	Connection	Aluminum Part #	Price/E
2"	female cam	200DBAL	\$264.05
3"	female cam	300DBAL	276.10

Street Cleaning Nozzles

Features:

- delivers a flat, centered spray pattern for flushing or street cleaning apparatus
- length: 6¾", width: 8½"
- maximum operating pressure: **100 PSI** (water only)
- flows 300 GPM @ 100 PSI



Thread	Spray Direction	Brass Part #	Price/E
2½" NPSH	center	BFSCN250C	\$1701.00
2½" NPSH	left	BFSCN250L	1701.00
2½" NPSH	right	BFSCN250R	1701.00